

INDUSTRIAL X-RAY FILM FIXER FOR AUTOMATIC PROCESSOR

PRODUCT CODE	850737 Part A: 2 x 5 litres HDPE bottles Part B: 1 x 1.125 litres HDPE bottle				
PRODUCT DESCRIPTION	FUJIFILM SUPER FI Fixer is high dilution source chemical designed for the processing of Industrial X-Ray Film in automatic process.				
PREPARATION	To make 38 litres of Fixer: 1) Pour 26.9 litres of water into the appropriate vessel 2) Add 2 bottles of part A and stir 3) Add 1 bottle of part B while stirring				
USAGE (AUTOMATIC PROCESSOR)	1) Pour the mixed fixer into the fixer tank of processor and remaining liquid can be used as the replenisher. The temperature recommended is 30 degree Celsius for fixing. Recommended replenishment rates of developer or fixer are: <table border="1" data-bbox="432 1249 919 1332"> <tr> <td>Developer</td> <td>55-70mL / 1000cm² film</td> </tr> <tr> <td>Fixer</td> <td>180-220mL / 1000cm² film</td> </tr> </table>		Developer	55-70mL / 1000cm ² film	Fixer
Developer	55-70mL / 1000cm ² film				
Fixer	180-220mL / 1000cm ² film				
STORAGE	FUJIFILM recommends storage of processing chemicals at 10 to 25 degree Celsius. The lower the temperature, the higher the possibilities of crystallisation of chemical. Oxidisation will occur if the solution is exposed to higher than recommended temperature. For a copy of the Material Safety Data Sheet: http://bit.ly/superfi850737				